



**“Give some bite to your engine!”**

# Cobra Diesel 10W Monograde Motor Oil

## Features and Benefits

- Multipurpose
- Low ash content, <1%
- Excellent hydraulic oil
- Combats corrosion & moisture

**Cobra Diesel 10W** is blended from select high viscosity base stocks and low-ash additives. This formulation has added detergent to ensure engine cleanliness, minimized ring-sticking and reduced liner-scuffing.

**Cobra Diesel 10W** prevents sludge formation, reduces bearing corrosion and cuts back on engine rusting.

**Cobra Diesel 10W** can be used as hydraulic oils where appropriate if extra care is taken not to mix them with regular hydraulic oils.



## Typical Results

TEST METHOD	DIESEL 10W
SAE GRADE	10W
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	39.0 6.6
VISCOSITY INDEX (D2270)	123
FLASH POINT (°C) (D93)	200
POUR POINT (°C) (D97)	-40
DENSITY @ 15°C (kg/L) (D4052)	0.86
TOTAL BASE NUMBER (mg KOH/g) (D2896)	7.3
ZINC (% Wt)	0.09

## Specifications

✓ Meets Requirements

SPECIFICATION	DIESEL 10W
API CF	✓
API SF	✓
Allison C4	✓
CAT TO-2	✓

## Sizes and Order Codes

SIZE	DIESEL 10W
18.9L / 5 US Gal Pail	FBB0009940



Supporting data available to demonstrate appropriate performance. Check with your Sales Representative for latest product approvals. Please note, these are typical performance indicators and can change without notice. This datasheet supersedes any previous version prior to May 3, 2022.

[www.irvingoil.com/en-CA/blending-packaging/cobra](http://www.irvingoil.com/en-CA/blending-packaging/cobra) for more information