# **TRAX**Multi-Use 2-Stroke Engine Oil



### **Features & Benefits**

- Low ash formulation
- Provides excellent system cleanliness
- Good low-temperature fluidity
- · Good film strength at high temperature
- · Will not stain pistons
- · Distinct blue identifying colour
- Vanilla Scented

# **Specifications**

✓ Meets Requirements

Specification	TRAX		
JASO FB, FC, FD	✓		
ISO-L-EGB, EGC, EGD	✓		
API TC	✓		

# **Typical Results**

Test Method	TRAX		
APPEARANCE	Blue		
SCENT	Vanilla		
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	45.6 7.6		
VISCOSITY INDEX (D2270)	133		
POUR POINT (D97) (°C)	-40		
FLASH POINT (D93) (°C)	93		
<b>DENSITY</b> @ <b>15°C</b> (D4052) (kg/L)	0.87		

#### Sizes & Order Codes

Size	TRAX
946 ml/1 US Qt	F0021015
1000 L/ 264 US Gal Bulk Tote	F0021001
Bulk	B0021001



**TRAX** is a high-performance low-ash lubricant developed for air and liquid-cooled 2-stroke gasoline engines formulated with a pleasant vanilla scent.

TRAX was formulated with a unique concentration of detergent and anti-wear additives to provide great lubricity with good corrosion and rust protection. Its low ash formulation helps to prevent crankcase, piston, and ring groove deposits.

**TRAX** meets the demanding exhaust system blocking levels of JASO FD and offers enhanced fuel oxidation stability to reduce varnish and gumming.

TRAX is recommended for chain saws, string trimmers, lawnmowers, snow blowers, motorcycles, ATVs, snowmobiles and other air or liquid-cooled 2-stroke gasoline engines where the manufacturer recommends a low-ash, JASO FD, ISO-L-EGD, or API TC oil.

**TRAX** oil meets the demanding requirements of Bombardier snowmobiles.

**TRAX** can be used in pre-mixed or oil-injected 2-stroke lubrication systems.

**Note:** TRAX is unsuitable for water-cooled outboard engines; please consider **2-Cycle Plus**.

www.irvingoil.com/lubricants 1.800.574.5823

www.irvingoil.com/lubricants 1.800.574.5823





## Ratios for TRAX to be Added to Gasoline

**Units: Metric** 

Gasoline	Ratio mL of TRAX to be added to gasoline					
	16:1	20:1	25:1	32:1	40:1	50:1
Litres	mL	mL	mL	mL	mL	mL
5	313	250	200	156	125	100
10	625	500	400	313	250	200
15	938	750	600	469	375	300
20	1250	1000	800	625	500	400
25	1563	1250	1000	781	625	500

## **Units: US Gallon & Fluid Ounce**

Gasoline	Ratio mL of TRAX to be added to gasoline					
	16:1	20:1	25:1	32:1	40:1	50:1
us gal.	fl. oz.	fl. oz.	fl. oz.	fl. oz.	fl. oz.	fl. oz.
1.32	10.6	8.5	6.8	5.3	4.2	3.4
2.64	21.1	16.9	13.5	10.6	8.5	6.8
3.96	31.7	25.4	20.3	15.9	12.7	10.1
5.28	42.3	33.8	27.1	21.1	16.9	13.5
6.60	52.8	42.3	33.8	26.4	21.1	16.9



www.irvingoil.com/lubricants 1.800.574.5823