



Stalube

High Performance Chain Oil

Features & benefits

- High quality base oils
- Dyed for easy visibility
- Extremely tacky
- Superior protection
- Multipurpose

Typical results

Test Method	Stalube 40	Stalube 185	Stalube 185 ND
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	43.7 7.8	183.2 18.1	183.2 18.1
VISCOSITY INDEX (D2270)	150	109	109
COLOUR	Red	Red	2.5 (D1500)
DENSITY @ 15°C (D4052), kg/L	0.86	0.89	0.89
POUR POINT (D97), °C	-36	-6	-6
FLASH POINT (D93), °C	187	227	227

Sizes & order codes

Size	Stalube 40	Stalube 185	Stalube 185 ND
205 L (54.2 US gal)	F0018650	F0015150	F0015050

Stalube Oils are high-performance chain oils formulated especially for heavy-duty applications with chain saws and in industrial machinery where drippage is unwanted, unsightly or hazardous.

Unlike many chain oils, **Stalube** is formulated using high quality paraffinic mineral base oils and blended into 2 grades suitable for a wide range of operating conditions both in-plants, outdoors and in any season.

Stalube is extremely tacky, which helps the oil stick where it is applied and resist drippage or throw-off, even from high-speed chains. This ensures unsurpassed protection and reduces consumption.

Stalube 40 is good for deep winter use, especially for the automatic chain lubricators on the heads of harvesters. This grade is formulated to maintain fluidity in extreme cold environments to -36C.

Stalube 185 is suitable for chain saws outside in summer weather.

Stalube 40 & 185 are dyed red to help operators check there is enough lubricant on the chain. **Stalube 185 ND (no dye)** version is also available.

