



TRANSflo

Automatic Transmission Fluid

Features & benefits

- Meets GM DEXRON®-III and Ford MERCON® requirements
- Excellent corrosion and foam prevention
- Safe for all seals
- Promotes transmission cleanliness
- Superior anti-wear protection



Typical results

Test Method	TRANSflo
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	31.7 7.1
VISCOSITY INDEX (D2270)	198
COLOUR	Red
DENSITY @ 15°C (D4052), kg/L	0.84
POUR POINT (D97), °C	-48
FLASH POINT (D93), °C	200
BROOKFIELD @ -40°C (D2983), cP	9,040

Sizes & order codes

Size	TRANSflo
946 mL (1 US QT)	F0020815
3.78 L (1 US gal)	F0020826
18.9 L (5 US gal)	F0082240
205 L (54.2 US gal)	F0015650
1000 L (264 US gal)	F0020860
Bulk	B0020801

TRANSflo is a premium product specially formulated for automatic transmissions in General Motors, Ford, and Chrysler vehicles manufactured in 2005 and earlier.

TRANSflo provides excellent low-temperature fluidity and maintains its film-thickness at temperatures over 149°C for bearing and gear lubrication.

TRANSflo meets Allison's specifications as a type C-4 fluid and can be used in Ford model C-6 automatic transmissions built on or after 1977.

TRANSflo can also be used in certain power steering, hydro-static systems, and power-shift transmissions, for which this type of oil is recommended.

TRANSflo may also be used as hydraulic fluid due to its excellent low-temperature fluidity and red colour.

TRANSflo should not be used in applications calling for MERCON® V, Type F, DCT or CVT fluids.



Always consult your owner's manual for verification of fluid type and grade.
Check with sales associate for the latest product approvals and acceptable performance data.
Please note these are typical performance indicators and can change without notice.
This data sheet replaces previous versions prior to November 8, 2024.
www.irvingoil.com/lubricants • 1.800.574.5823



TRANSflo

Automatic Transmission Fluid

Specifications

✓ Meets requirements

Specification	TRANSflo
Allison C-3, C-4	✓
Allison TES-389	✓
American Motors ATF +3 (MS 7176-E)	✓
Audi 5HP LT71141	✓
Audi G 052 162-A1/A2 (ZF Lifeguard 5)	✓
BMW 7045E, ETL-8072B, LA2634	✓
CAT TO-2	✓
Chrysler ATF+2, +3	✓
Ford MERCON®	✓
Ford WSS M2C 138CJ, 166H	✓
GM DEXRON®-II, -IID, -IIE, -IIIG, -IIIH	✓
GM TASA	✓
Hyundai/Kia DEX-II/SP-II	✓
Jaguar JLM 20292, 20238	✓
Mazda ATF M-III, & F-I	✓
MB ZF 4HP20	✓
NAG 1 (Chrysler, Jeep, Cherokee)	✓
Opel/GM 19 40 700, 19 40 767, 21005966 Transaxle, 22 17466	✓
Peugot/Citreon Z 000169756, AL4 Automatic gearbox oil (#9730.AE)	✓
Porsche 000 043 205 09, 999 917 547 00, Z 000169756	✓
Renault Matic D2, DPO/AL4	✓
Volvo CE 97340	✓
Volvo 97325 & 97335	✓
Vickers M2950-S, I-286-S	✓
VW G US 000 162	✓
ZF TE-ML 05L, 09, 21L	✓



Always consult your owner's manual for verification of fluid type and grade.
Check with sales associate for the latest product approvals and acceptable performance data.
Please note these are typical performance indicators and can change without notice.
This data sheet replaces previous versions prior to November 8, 2024.
www.irvingoil.com/lubricants • 1.800.574.5823